

B/FX Braze Paste

Cat.-No. 0408

Ready-to-use braze paste

EN 1045 type: FH21

Added customer value

- Ready-to-use braze paste
- Large application spectrum
- Easy to handle
- Working temperature from 580 °C to 1000 °C
- For copper-phosphorus solders



Technical data

| | |
|------------------|-----------------------|
| Appearance | paste, white |
| Processing | homogenize before use |
| Water solubility | conditionally soluble |
| Durability | 12 months |

Application area

Hard soldering
of copper and brass
materials

Packaging units

- | | | |
|---|--|--|
| <input checked="" type="checkbox"/> Tins / 250 ml | <input checked="" type="checkbox"/> Metering bottle / ml | <input type="checkbox"/> Spray bottle / ml |
| <input type="checkbox"/> Granulate / Size | <input type="checkbox"/> Metering pen / ml | <input type="checkbox"/> Injection / ml |

EMIL OTTO Flux- und Oberflächentechnik GmbH
D-65346 Eltville – Eltviller Landstr. 22
Tel.: +49 (0)6123 / 70 46 0 – Fax: +49 (0)6123 / 70 46 15



The data given in our descriptions are typical values. They are provided for your information, but do not represent specifications or assurances of properties in the sense of liability and warranty claims. The same applies to the application-related information; these are non-binding and do not release our customers from their own testing of our products for their suitability for the intended purpose Process or purpose.